

NUSC Technical Document 8733
24 May 1990

AD-A223 883

Measuring the Vertical Directional Spectra Caused by Sea Surface Sound

A Paper Presented at the 119th Meeting of the
Acoustical Society of America, State College,
Pennsylvania, 24 May 1990

R.M. Kennedy
Test and Evaluation Department
West Palm Beach, Florida



DTIC
ELECTE
JUL 17 1990
S E D

Naval Underwater Systems Center
Newport, Rhode Island • New London, Connecticut

Approved for public release; distribution is unlimited.

PREFACE

This report was prepared under Project S64838 and 638V11, Principal Investigator R.M. Kennedy (Code 3802). The work reported herein was performed as part of the Naval Underwater Systems Center program of Independent Research and Independent Exploratory Development (IR/IED), Program Manager Dr. K.M. Lima, and the Test and Evaluation Department Acoustic Range Initiative, Program Manager J.H. Keegan.

The Technical Reviewer for this report was A.B. Caron (Code 3802) whose contributions to the document are gratefully acknowledged.

Reviewed and Approved: May 1990



J.H. Keegan, Code 38
Head, Test and Evaluation Department

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release, distribution is unlimited.	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE				
4. PERFORMING ORGANIZATION REPORT NUMBER(S) TD 8733				
6a. NAME OF PERFORMING ORGANIZATION Naval Underwater Systems Center Detachment		6b. OFFICE SYMBOL (If applicable) 3802	7a. NAME OF MONITORING ORGANIZATION	
6c. ADDRESS (City, State, and ZIP Code) West Palm Beach, FL 33402			7b. ADDRESS (City, State, and ZIP Code)	
8a. NAME OF FUNDING / SPONSORING ORGANIZATION Naval Underwater Systems Center		8b. OFFICE SYMBOL (If applicable) 38	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code) Newport, RI 02841			10. SOURCE OF FUNDING NUMBERS	
			PROGRAM ELEMENT NO.	PROJECT NO. 638V11
			TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) Measuring the Vertical Directional Spectra Caused by Sea Surface Sound				
12. PERSONAL AUTHOR(S) Kennedy, R.M.				
13a. TYPE OF REPORT Lecture Transcript		13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 1990 May 24	15. PAGE COUNT 31
16. SUPPLEMENTARY NOTATION Presentation to the 119th Meeting of the Acoustical Society of America				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Underwater Acoustics	
FIELD	GROUP	SUB-GROUP		
17	01			
19. ABSTRACT (Continue on reverse if necessary and identify by block number) See reverse side.				
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL R.M. Kennedy			22b. TELEPHONE (Include Area Code) (407) 832-8566	22c. OFFICE SYMBOL 3802

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

19. ABSTRACT

The objective of the measurements discussed here is the development of a database of directional spectra obtained in an acoustically isolated area (Tongue of the Ocean, The Bahamas) where the acoustic ambient is principally controlled by the local (observable) sea surface conditions. The purpose of the database is the identification of a model of the space-time statistics of sea surface sound. A wideband (40 to 4000 Hz) vertical acoustic linear antenna system was used. Data logging took place in a remote, autonomously operating subsurface buoy system. Recording restrictions limited each of the seven octavely nested apertures of the sensor system to four wavelengths. However, quite adequate spatial resolutions of the directional spectral estimates were obtained using a physically based parametric model of the random process. The results of the initial two-month deployment (wind speed range of 2 to 16 m/s) are discussed here. The measured directional spectra are displayed as a function of frequency, elevation angle, and surface friction velocity. The sea surface sound source structure is discussed.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

This document is a transcript of the presentation given by Dr. Kennedy on May 24, 1990, at the 119th Meeting of the Acoustical Society of America, which was sponsored by Pennsylvania State University, in State College, PA.

Accession For	
1. AS 1191	<input checked="checked" type="checkbox"/>
2. AS 1192	<input type="checkbox"/>
3. AS 1193	<input type="checkbox"/>
4. AS 1194	
5. AS 1195	
6. AS 1196	
7. AS 1197	
8. AS 1198	
9. AS 1199	
10. AS 1200	
11. AS 1201	
12. AS 1202	
13. AS 1203	
14. AS 1204	
15. AS 1205	
16. AS 1206	
17. AS 1207	
18. AS 1208	
19. AS 1209	
20. AS 1210	
21. AS 1211	
22. AS 1212	
23. AS 1213	
24. AS 1214	
25. AS 1215	
26. AS 1216	
27. AS 1217	
28. AS 1218	
29. AS 1219	
30. AS 1220	
31. AS 1221	
32. AS 1222	
33. AS 1223	
34. AS 1224	
35. AS 1225	
36. AS 1226	
37. AS 1227	
38. AS 1228	
39. AS 1229	
40. AS 1230	
41. AS 1231	
42. AS 1232	
43. AS 1233	
44. AS 1234	
45. AS 1235	
46. AS 1236	
47. AS 1237	
48. AS 1238	
49. AS 1239	
50. AS 1240	
51. AS 1241	
52. AS 1242	
53. AS 1243	
54. AS 1244	
55. AS 1245	
56. AS 1246	
57. AS 1247	
58. AS 1248	
59. AS 1249	
60. AS 1250	
61. AS 1251	
62. AS 1252	
63. AS 1253	
64. AS 1254	
65. AS 1255	
66. AS 1256	
67. AS 1257	
68. AS 1258	
69. AS 1259	
70. AS 1260	
71. AS 1261	
72. AS 1262	
73. AS 1263	
74. AS 1264	
75. AS 1265	
76. AS 1266	
77. AS 1267	
78. AS 1268	
79. AS 1269	
80. AS 1270	
81. AS 1271	
82. AS 1272	
83. AS 1273	
84. AS 1274	
85. AS 1275	
86. AS 1276	
87. AS 1277	
88. AS 1278	
89. AS 1279	
90. AS 1280	
91. AS 1281	
92. AS 1282	
93. AS 1283	
94. AS 1284	
95. AS 1285	
96. AS 1286	
97. AS 1287	
98. AS 1288	
99. AS 1289	
100. AS 1290	
101. AS 1291	
102. AS 1292	
103. AS 1293	
104. AS 1294	
105. AS 1295	
106. AS 1296	
107. AS 1297	
108. AS 1298	
109. AS 1299	
110. AS 1300	
111. AS 1301	
112. AS 1302	
113. AS 1303	
114. AS 1304	
115. AS 1305	
116. AS 1306	
117. AS 1307	
118. AS 1308	
119. AS 1309	
120. AS 1310	
121. AS 1311	
122. AS 1312	
123. AS 1313	
124. AS 1314	
125. AS 1315	
126. AS 1316	
127. AS 1317	
128. AS 1318	
129. AS 1319	
130. AS 1320	
131. AS 1321	
132. AS 1322	
133. AS 1323	
134. AS 1324	
135. AS 1325	
136. AS 1326	
137. AS 1327	
138. AS 1328	
139. AS 1329	
140. AS 1330	
141. AS 1331	
142. AS 1332	
143. AS 1333	
144. AS 1334	
145. AS 1335	
146. AS 1336	
147. AS 1337	
148. AS 1338	
149. AS 1339	
150. AS 1340	
151. AS 1341	
152. AS 1342	
153. AS 1343	
154. AS 1344	
155. AS 1345	
156. AS 1346	
157. AS 1347	
158. AS 1348	
159. AS 1349	
160. AS 1350	
161. AS 1351	
162. AS 1352	
163. AS 1353	
164. AS 1354	
165. AS 1355	
166. AS 1356	
167. AS 1357	
168. AS 1358	
169. AS 1359	
170. AS 1360	
171. AS 1361	
172. AS 1362	
173. AS 1363	
174. AS 1364	
175. AS 1365	
176. AS 1366	
177. AS 1367	
178. AS 1368	
179. AS 1369	
180. AS 1370	
181. AS 1371	
182. AS 1372	
183. AS 1373	
184. AS 1374	
185. AS 1375	
186. AS 1376	
187. AS 1377	
188. AS 1378	
189. AS 1379	
190. AS 1380	
191. AS 1381	
192. AS 1382	
193. AS 1383	
194. AS 1384	
195. AS 1385	
196. AS 1386	
197. AS 1387	
198. AS 1388	
199. AS 1389	
200. AS 1390	
201. AS 1391	
202. AS 1392	
203. AS 1393	
204. AS 1394	
205. AS 1395	
206. AS 1396	
207. AS 1397	
208. AS 1398	
209. AS 1399	
210. AS 1400	
211. AS 1401	
212. AS 1402	
213. AS 1403	
214. AS 1404	
215. AS 1405	
216. AS 1406	
217. AS 1407	
218. AS 1408	
219. AS 1409	
220. AS 1410	
221. AS 1411	
222. AS 1412	
223. AS 1413	
224. AS 1414	
225. AS 1415	
226. AS 1416	
227. AS 1417	
228. AS 1418	
229. AS 1419	
230. AS 1420	
231. AS 1421	
232. AS 1422	
233. AS 1423	
234. AS 1424	
235. AS 1425	
236. AS 1426	
237. AS 1427	
238. AS 1428	
239. AS 1429	
240. AS 1430	
241. AS 1431	
242. AS 1432	
243. AS 1433	
244. AS 1434	
245. AS 1435	
246. AS 1436	
247. AS 1437	
248. AS 1438	
249. AS 1439	
250. AS 1440	
251. AS 1441	
252. AS 1442	
253. AS 1443	
254. AS 1444	
255. AS 1445	
256. AS 1446	
257. AS 1447	
258. AS 1448	
259. AS 1449	
260. AS 1450	
261. AS 1451	
262. AS 1452	
263. AS 1453	
264. AS 1454	
265. AS 1455	
266. AS 1456	
267. AS 1457	
268. AS 1458	
269. AS 1459	
270. AS 1460	
271. AS 1461	
272. AS 1462	
273. AS 1463	
274. AS 1464	
275. AS 1465	
276. AS 1466	
277. AS 1467	
278. AS 1468	
279. AS 1469	
280. AS 1470	
281. AS 1471	
282. AS 1472	
283. AS 1473	
284. AS 1474	
285. AS 1475	
286. AS 1476	
287. AS 1477	
288. AS 1478	
289. AS 1479	
290. AS 1480	
291. AS 1481	
292. AS 1482	
293. AS 1483	
294. AS 1484	
295. AS 1485	
296. AS 1486	
297. AS 1487	
298. AS 1488	
299. AS 1489	
300. AS 1490	
301. AS 1491	
302. AS 1492	
303. AS 1493	
304. AS 1494	
305. AS 1495	
306. AS 1496	
307. AS 1497	
308. AS 1498	
309. AS 1499	
310. AS 1500	
311. AS 1501	
312. AS 1502	
313. AS 1503	
314. AS 1504	
315. AS 1505	
316. AS 1506	
317. AS 1507	
318. AS 1508	
319. AS 1509	
320. AS 1510	
321. AS 1511	
322. AS 1512	
323. AS 1513	
324. AS 1514	
325. AS 1515	
326. AS 1516	
327. AS 1517	
328. AS 1518	
329. AS 1519	
330. AS 1520	
331. AS 1521	
332. AS 1522	
333. AS 1523	
334. AS 1524	
335. AS 1525	
336. AS 1526	
337. AS 1527	
338. AS 1528	
339. AS 1529	
340. AS 1530	
341. AS 1531	
342. AS 1532	
343. AS 1533	
344. AS 1534	
345. AS 1535	
346. AS 1536	
347. AS 1537	
348. AS 1538	
349. AS 1539	
350. AS 1540	
351. AS 1541	
352. AS 1542	
353. AS 1543	
354. AS 1544	
355. AS 1545	
356. AS 1546	
357. AS 1547	
358. AS 1548	
359. AS 1549	
360. AS 1550	
361. AS 1551	
362. AS 1552	
363. AS 1553	
364. AS 1554	
365. AS 1555	
366. AS 1556	
367. AS 1557	
368. AS 1558	
369. AS 1559	
370. AS 1560	
371. AS 1561	
372. AS 1562	
373. AS 1563	
374. AS 1564	
375. AS 1565	
376. AS 1566	
377. AS 1567	
378. AS 1568	
379. AS 1569	
380. AS 1570	
381. AS 1571	
382. AS 1572	
383. AS 1573	
384. AS 1574	
385. AS 1575	
386. AS 1576	
387. AS 1577	
388. AS 1578	
389. AS 1579	
390. AS 1580	
391. AS 1581	
392. AS 1582	
393. AS 1583	
394. AS 1584	
395. AS 1585	
396. AS 1586	
397. AS 1587	
398. AS 1588	
399. AS 1589	
400. AS 1590	
401. AS 1591	
402. AS 1592	
403. AS 1593	
404. AS 1594	
405. AS 1595	
406. AS 1596	
407. AS 1597	
408. AS 1598	
409. AS 1599	
410. AS 1600	
411. AS 1601	
412. AS 1602	
413. AS 1603	
414. AS 1604	
415. AS 1605	
416. AS 1606	
417. AS 1607	
418. AS 1608	
419. AS 1609	
420. AS 1610	
421. AS 1611	
422. AS 1612	
423. AS 1613	
424. AS 1614	
425. AS 1615	
426. AS 1616	
427. AS 1617	
428. AS 1618	
429. AS 1619	
430. AS 1620	
431. AS 1621	
432. AS 1622	
433. AS 1623	
434. AS 1624	
435. AS 1625	
436. AS 1626	
437. AS 1627	
438. AS 1628	
439. AS 1629	
440. AS 1630	
441. AS 1631	
442. AS 1632	
443. AS 1633	
444. AS 1634	
445. AS 1635	
446. AS 1636	
447. AS 1637	
448. AS 1638	
449. AS 1639	
450. AS 1640	
451. AS 1641	
452. AS 1642	
453. AS 1643	
454. AS 1644	
455. AS 1645	
456. AS 1646	
457. AS 1647	
458. AS 1648	
459. AS 1649	
460. AS 1650	
461. AS 1651	
462. AS 1652	
463. AS 1653	
464. AS 1654	
465. AS 1655	
466. AS 1656	
467. AS 1657	
468. AS 1658	
469. AS 1659	
470. AS 1660	
471. AS 1661	
472. AS 1662	
473. AS 1663	
474. AS 1664	
475. AS 1665	
476. AS 1666	
477. AS 1667	
478. AS 1668	
479. AS 1669	
480. AS 1670	
481. AS 1671	
482. AS 1672	
483. AS 1673	
484. AS 1674	
485. AS 1675	
486. AS 1676	
487. AS 1677	
488. AS 1678	
489. AS 1679	
490. AS 1680	
491. AS 1681	
492. AS 1682	
493. AS 1683	
494. AS 1684	
495. AS 1685	
496. AS 1686	
497. AS 1687	
498. AS 1688	
499. AS 1689	
500. AS 1690	
501. AS 1691	
502. AS 1692	
503. AS 1693	
504. AS 1694	
505. AS 1695	
506. AS 1696	
507. AS 1697	
508. AS 1698	
509. AS 1699	
510. AS 1700	
511. AS 1701	
512. AS 1702	
513. AS 1703	
514. AS 1704	
515. AS 1705	
516. AS 1706	
517. AS 1707	
518. AS 1708	
519. AS 1709	
520. AS 1710	
521. AS 1711	
522. AS 1712	
523. AS 1713	
524. AS 1714	
525. AS 1715	
526. AS 1716	
527. AS 1717	
528. AS 1718	
529. AS 1719	
530. AS 1720	
531. AS 1721	
532. AS 1722	
533. AS 1723	
534. AS 1724	
535. AS 1725	
536. AS 1726	
537. AS 1727	
538. AS 1728	
539. AS 1729	
540. AS 1730	
541. AS 1731	
542. AS 1732	
543. AS 1733	
544. AS 1734	
545. AS 1735	
546. AS 1736	
547. AS 1737	
548. AS 1738	
549. AS 1739	
550. AS 1740	
551. AS 1741	
552. AS 1742	
553. AS 1743	
554. AS 1744	
555. AS 1745	
556. AS 1746	
557. AS 1747	
558. AS 1748	
559. AS 1749	

SLIDE 1: (1.5 minutes)

Both the design and the analysis of underwater acoustic systems are dependent on good models of the local acoustic ambient. It is well known that the sea surface generates acoustic radiation that often dominates the system output noise field, and despite considerable effort, improvements in the models remain necessary when hydrophone arrays having vertical apertures are used in a wide range of environments. The objective of the task that I am discussing is the development of a model of the vertical directional spectrum due to that sea-surface-generated radiation. Directional spectra has been chosen because it is a readily visualized statistic that is physically intuitive and has proven useful in the design and analysis of underwater acoustic systems.

The present state of the theory of sea surface sound is such that the model development is necessarily experimentally based.¹ While several measurements of the directivity function have been made, it has proven difficult to make this measurement in such a way that the near horizontally directed energy is not significantly affected by long-distance sources that complicate the modeling process.² A theme in the data processing, which I will describe, is that having the total directional spectra determined by the local sea surface condition allows one to partition the measurement into more than a single source type because the source types distinguish themselves by their directional patterns.

The approach this project took was to build a database of directional spectra measured in an acoustically isolated area where the acoustic ambient is dominated by the local sea conditions.

PROJECT OBJECTIVE

- Develop Model Of Acoustic Ambient Vertical Directional Spectrum Due To Sea Surface Sound.

PROBLEM STATEMENT

- Present Directional Spectrum Measurements Frequently Contain Long-Distance Sources Which Complicate Modeling Process.

PROJECT APPROACH


- Accumulate Database From An Acoustically Isolated Area With It's Acoustic Ambient Dominated By Well Documented Local Wind And Sea Conditions.

SLIDE 2: (1 minute)

The Tongue of the Ocean (TOTO), The Bahamas, is the location of the measurement. It is a relatively deep water basin that is totally isolated from global shipping. This figure, with the depth contours in fathoms, shows that the shallowest area is 700 fathoms, or 1300 meters, deep. This is deep enough in wavelengths not to act as a shallow water location but shallow enough to have a lossy "bottom-limited" propagation characteristic within the basin itself. The Naval Underwater Systems Center has a presence in TOTO which makes available environmental monitoring locations and ready access to small vessels for servicing the acoustic measurement system.

Two measurement locations have been used. The initial two-month deployment of the measurement system was at a near reef-site close to Fresh Creek. The location was chosen for logistic reasons to service the initial wetting down of the system. The present location of the system is on the east side of the cul-de-sac. This location is further shielded from transiting vessels in TOTO by the land mass north of the location. Ten months of the planned one-year deployment have been completed. Note that the diameter of the cul-de-sac is a little more than 30 nmi.

MEASUREMENT LOCATION



SLIDE 3: (2 minutes)

The measurement system objective was a broadband characterization of the diffuse acoustic ambient field. The Naval Underwater Systems Center IR/IED sponsor required that the system be quite low cost. The system that you see in this figure is the resulting compromise. The dilemma of the acoustic antenna design is that over much of the angular range the diffuse ambient changes slowly with vertical angle and a low-resolution system is adequate, but near the horizontal direction, where media refraction can abruptly change the solid-angle density function, a considerably higher resolution system is necessary. The fielded system covered the two-decade frequency band shown with a modest 2- to 4-wavelength aperture. A parametric spectral estimation algorithm that models the media refraction was then used to obtain the higher angular resolution near the horizontal direction.


The seven octaves are recorded sequentially by synchronously recording the eight 14-bit hydrophone signals from each section on three video cassette recorders. Also recorded are the depth and tilt of the vertical hydrophone array. After the 21-minute recording period the system sleeps for 50 hours before it repeats the cycle. Every 45 to 50 days it is necessary to retrieve the system to replenish the 3 VCR tapes and 96 flashlight batteries that power the electronics.

The brightly colored syntactic foam collar around the instrumented pressure vessel maintains the verticality of the system within a small fraction of the hydrophone array angular resolution.


INSTRUMENTATION SUMMARY



FLOTATION
VCR RECORDER,
BATTERIES, CONTROL




7 'NESTED' OCTAVES,
40 - 4000 Hz,
2 - 4 λ



SLIDE 4: (1 minute)

The basic statistic measured is the hydrophone cross-spectral density (CSD) matrix. However, because the CSD matrix is not a readily visualized quantity, it is useful to calculate, from the CSD matrix, a beamformed output that is displayed and examined to determine the quality of each measurement. This figure illustrates the "direction of arrival spectrum" in $(\text{dB}/\mu\text{Pa}^2/\text{Hz})$ as a function of frequency and elevation angle. The contour plot on the left gives quantitative details, and the surface plot on the right gives a qualitative view of the entire surface. Note that zero degrees is looking straight up at the water surface. The figure is a composite of all seven octaves; the high frequency end of each aperture is visually "flagged" by the aliasing lobe that occurs at the frequency for which the hydrophones are spaced one-half wavelength apart. Note also that in the horizontal direction, i.e., at an elevation angle of 90 degrees, a clear refractive notch is evident at high frequencies despite the low angular resolution of the measurement system.

EXAMINING RAW DATA



-18 - -15


-21 - -19

-24 - -22

-30 - -28

-33 - -31

-36 - -34



SLIDE 5: (2.5 minutes)

The overall characteristics of the vertical directional spectra as a function of the sea surface condition are illustrated here. These figures represent first-order estimates of the directional spectrum formed by simply normalizing the beamformed output by the solid-angle coverage of the major lobe and then averaging the spectral levels over one-third-octave bands. The ordinate of these figures is the directional spectrum in $(\text{dB}/\mu\text{Pa}^2/\text{Hz}/\text{steradian})$. The two independent variables are again frequency and elevation angle, with zero degrees looking up at the water surface. Except for the refractive "notch" area surrounding the horizontal direction, these first-order estimates are quantitatively quite correct and were obtained in the initial near-reef deployment. Higher order estimates of the directional spectra will be discussed shortly but are not necessary for the present discussion.


The measurement used to describe the sea surface condition is a nondimensional surface friction velocity.³ Wind speed measurements made 10 meters above the water surface were converted to surface friction velocity and then nondimensionalized by the minimum phase velocity of the water surface capillary-gravity wave field. A unity value of the nondimensional friction velocity is interpreted as the point of incipient whitecapping.

The following aspects of the data should be noted. First, with whitecaps present the measured vertical directional spectrum in the direction of the sea surface is a smooth surface with a rather flat maximum in the direction of the surface at 500 Hz. This surface extends over the entire frequency range of the measurement. Second, without whitecaps present but with nondimensional friction velocity greater than one-half, the shape of the measured directional spectrum surface above its maximum value at 500 Hz remains unchanged although the height of the surface falls with the third power of the friction velocity. Below 200 to 400 Hz the surface falls rapidly with a reduction in frequency. Third, with the nondimensional friction velocity less than one-half, the measured directional spectrum is dominated by the modal behavior of the TOTO channel, not the local sea surface; i.e., the sea surface radiation is no longer being measured. Fourth, below 100 Hz the data


are frequently contaminated by "tones" radiating over a large horizontal extent of the escarpment. The last observation is characteristic of the near-reef site data only.

DIRECTIONAL SPECTRA WITH WHITECAPS PRESENT

$$u_w/u_c = 1.18$$




$$u_w/u_c = 1.81$$




DIRECTIONAL SPECTRA WITH NO WHITECAPS PRESENT

$$u_w/u_c = 0.32$$



$$u_w/u_c = 0.68$$



SLIDE 6: (3 minutes)

There are three reasons for choosing a parametric spectral estimation approach. First, if an appropriate bases function set exists then quite efficient parameterization of a complex field variable statistic is possible. Second, an increase in spectral resolution over nonparametric algorithms is possible. Third, physical interpretation of data can be enhanced if physical interpretation of the model is possible. For all these reasons, a model fit to the data was attempted. The model development is ad hoc and the components of the model occur historically in the acoustic ambient literature. This illustration is an attempt at quickly summarizing the ingredients of the model-fitting procedure. The actual mathematics are very straightforward.


All three of the components pictured, or at least some modified version of them, have been used individually in other studies.^{4,5} What is unique to the present approach is that more than one source type is assumed present and the data are then used to assign a strength to each one individually. The three components are (1) a plane of statistically independent vertical dipoles located at the sea surface, (2) a volume of statistically independent monopoles exponentially distributed in depth below a smooth pressure release surface, and (3) an isotropic term intended as a "catchall" component to include such things as scattering from media nonhomogeneities. The first two sources are propagated to the receiving system using a multipath expansion of a wave equation solution. This allows the modeled terms to be given an angular distribution. This was realized using the "generic sonar model" software package. Depending on the frequency, either BLUG or MGS bottom loss values were used. The effects of the hydrophone spatial sampling and finite aperture are included in the model.

The parameters representing the source area density occur linearly in the model, and the exponential depth scale occurs nonlinearly. Because the volume and surface source terms become indistinguishable from each other as the depth scale goes to zero, an iterative parameter estimation scheme was used to ensure orthogonality in the parameters. The result is that a volume

source term becomes significant only if the depth scale is of the order of a wavelength or greater.

Note also that if a contaminating plane wave is present in the data it also is readily accounted for in the fit to data but is ignored in the reconstruction of the directional spectrum.

PARAMETRIC MODEL SUMMARY



$$[\text{DIRECTIONAL MODEL}] = [\text{PLANAR DIPOLES}] + [\text{VOLUME MONOPOLES}] + [\text{ISOTROPIC SCATTER}]$$







SLIDE 7: (1 minute)

An important indication of the quality of the model is how well it fits the data. This figure shows an example of the model-data comparison at the beamformed output. In each panel the abscissa is the elevation angle steered to and the ordinate is the beamformed output. In the direction of the surface, i.e., between 0 and 90 degrees, which is the process we wish to model, the fit is nearly always within 1 dB of the data. The standard error for the "fit to data" as well as the standard error of parameter estimates is typically less than 5 percent. The cross-correlation coefficient between parameter estimates is always less than one-tenth.

Note that in the upper left-hand panel there existed a "target", i.e., a plane wave contaminating the data. A plane wave component added to the model readily fit the data.

MODEL-DATA COMPARISON

$$u_x/u_c = 1.8$$





SLIDE 8: (3/4 minute)

This figure shows an example of a measured vertical directional spectrum employing the parametric spectral estimation described. The measurement is from the cul-de-sac deployment with no whitecaps present. As before, the ordinate is the solid-angle density function illustrated as a function of log frequency from 40 to 4000 Hz and elevation angle from straight up to straight down. The direction of the sea surface is on the right-hand side. The refractive "notch" with its frequency-dependent depth is quite evident. Because the notch depth increases with frequency, it is most likely due to TOTO modal response rather than scattering.

VERTICAL DIRECTIONAL SPECTRUM


$$u_s/u_c = 0.83$$



SLIDE 9: (3/4 minute)

In this figure I have plotted the dipole coefficient, which is a source area density term, as a function of frequency with nondimensional friction velocity as a parameter. The following two characteristics are worth noting: First, for nondimensional friction velocity greater than one-half, the source density is inversely dependent on the first power of frequency above 1 kHz and independent of frequency below 1 kHz until a lower frequency cutoff is reached. The source strength is proportional to the third power of the friction velocity without whitecaps and the second power with whitecaps. The second observation is that for nondimensional friction velocity less than one-half, either the source strength is falling faster than the third power of the friction velocity and is below the background level, or the dipole component is only erratically present.

DIPOLE COEFFICIENT SUMMARY



SLIDE 10: (1 minute)

I will now summarize. The objective of this project is to model the vertical directional spectra due to sea surface sound alone. The approach taken is to accumulate a database obtained in an acoustically isolated area in which the acoustic ambient is dominated by the local sea conditions. To do this, a low-cost vertical hydrophone array operating from 40 to 4000 Hz has been operating in the Tongue of the Ocean, The Bahamas, for over a year. A data processing system has been designed and implemented that features a particularly efficient parameterization of the measured directional spectra. The physically based parametric model used in the spatial spectral estimation process has given some anecdotal evidence of the character of the sea surface sound source structure. A statistically based examination of the data is underway. The measurement period will be completed in July of this year. So far, 140 trials have been recorded.

SUMMARY

- Low-Cost Broadband Vertical Hydrophone Array And Data Recording System Designed And Installed In An Isolated Area.
- Data-Processing System Designed And Implemented To Efficiently Process Data Sets.
- Unique Database (>140 Data Sets) Accumulating To Examine Statistics Of Sea Surface Sound Source Structure.
- Physically Based Parametric Model Used To Improve Angular Resolution Of Directional Spectra.

REFERENCES

1. Sea Surface Sound, edited by B.R. Kerman, Kluwer Academic Publishers, Boston, MA, 1988.
2. W.A. Von Winkle and D.G. Browning, Vertical Noise Directionality in the Deep Ocean: A Review, NUSC Technical Document 7561, Naval Underwater Systems Center, Newport, RI, 1985.
3. B.R. Kerman, "Underwater Sound Generation by Breaking Waves," Journal of the Acoustical Society of America, vol. 75, 1984, p 148.
4. J.E. Ffowcs Williams and Y.P. Guo, "Mechanisms of Sound Generation at the Ocean Surface," Sea Surface Sound, edited by B.R. Kerman, Kluwer Academic Publishers, Boston, MA, 1988.
5. R.D. Hallett and R.M. Heitmeyer, "Noise Generation by Bubbles Formed in Breaking Waves," Sea Surface Sound, edited by B.R. Kerman, Kluwer Academic Publishers, Boston, MA, 1988.

INITIAL DISTRIBUTION LIST

<u>Addressee</u>	<u>Number of Copies</u>
COMNAVSEASYS COM (Code 63D) CDR E. Graham	1
(PMS393A) CDR S. Logue	1
(PMS393N) J.H. Fuchs	1
COMNAVAIRSYS COM (Code 421) T. Ramirez	1
CNA	1
DARPA Dr. A. Ellinthorpe	1
DTIC	12
DTRC (Code 1925) G.M. Jebsen	1
(Code 0100) R.E. Metrey	1
NAVPGSCOL H. Medwin	2
NOAA/Miami Dr. J. Prony, H. Bezdek	2
NOARL Dr. B. Adams	1
NOSC J. Rohn	1
OCNR (Code 1121GS) O. Brandt	1
(Code 1122ML) M. Briscoe	1
(Code 1125) L.G. Johnson	1
(Code 1125AR) R.F. Obrachta	1
(Code 11250A) M. Orr	1
Applied Measurement Systems, Inc., Hollywood, FL;	
B.L. Douglass	1
General Electric Co., Andros Island, Bahamas;	
L.A. Lindquist	1
GRD Associates, Delray Beach, FL;	
G.R. Desmarais	1
Planning Systems, Inc., New London, CT; W.M. Leen	1
MPL, Scripps Institution of Oceanography, La Jolla, CA;	
W. Hodgekist	1
University of Miami, Coral Gables, FL; Dr. F. Tappert	1